



# JA-162PW Wireless dual PIR and MW motion detector

This product is a wireless device of the JABLOTRON 100+ system. It is designed to detect human body movement inside buildings. A high immunity to false alarms is reached thanks to the combination of PIR and microwave (MW) detection. The detector works like a classic PIR detector, however, when the PIR detects movement in a guarded area, the MW part is activated and confirms the previous PIR activation.

o [Declaration of conformity - JA-162PW \(PDF 683.21 kB\)](#)



## Description

The detector features a white lens that provides standard white light immunity as defined by the norm (up to 6000 lux). The immunity to false alarms can be set at two levels, PIR and MW. The detector operates with a pulse reaction and takes up a single position in the system.

**This device is only compatible with the JA-103K and JA-107K control panels.**

## Technical specifications

<b>Power supply</b>	2x lithium battery, type: CR123A (3 V/1500 mAh) Please note: Batteries are not included.
<b>Typical lifetime of batteries</b>	4 Years
<b>LowBatt state</b>	< 2,7 V
<b>Quiescent current consumption</b>	65 µA
<b>Maximum current consumption</b>	50 mA
<b>Communication band</b>	868,1 MHz, JABLOTRON protocol
<b>Maximum radio-frequency power (ERP)</b>	25 mW
<b>Communication range</b>	cca 300 m (open area)
<b>Recommended installation height</b>	2.2 - 2.5 m above floor level
<b>Detection angle/detection coverage PIR</b>	90°/12 m
<b>Detection angle/detection coverage MW</b>	80°/12 m
<b>Operational frequency MW</b>	24,125 GHz
<b>Maximum radio-frequency power (ERP)</b>	30 mW
<b>Dimensions</b>	63 x 150 x 40 mm

<b>Weight (w/o batteries)</b>	125 g
<b>Classification</b>	Security grade 2/Environmental class II (according to EN 50131-1)
<b>Operating temperature range</b>	-10 °C to +40 °C
<b>Average operating humidity</b>	75 % RH, w/o condensation
<b>Certification body</b>	Trezor Test s.r.o. (no. 3025)
<b>In compliance with</b>	ETSI EN 300 220-1,-2, ETSI EN 300 440, EN 50130-4, EN 55032, EN 62368-1, EN 50581, EN 50131-1, EN 50131-2-4, EN 50131-5-3, EN 50131-6
<b>Operating conditions according to general authorization</b>	ERC REC 70-03