



## JA-154A Wireless battery indoor siren

The wireless siren can be easily mounted anywhere within range of the system radio. Flexible installation is made possible by power from 3 AA batteries.

○ [Declaration of conformity - JA-154A \(PDF 540.8 kB\)](#)


### Technical specifications

<b>Power</b>	3x Alkaline battery, type LR6 (AA) 1.5 V/2.45 Ah Batteries are not included in the packaging.
<b>Typical lifetime of batteries</b>	approx. 2 years
<b>LowBatt state</b>	<3,3 V
<b>Quiescent current consumption</b>	135 $\mu$ A
<b>Maximum current consumption</b>	250 mA
<b>Current consumption during acoustic indication</b>	250 mA
<b>Communication frequency</b>	868.1 MHz, JABLOTRON protocol
<b>Maximum radio-frequency power (ERP)</b>	<25 mW
<b>Maximal acoustic output</b>	85-88 dB
<b>Type of warning device</b>	type W
<b>Dimensions</b>	100 x 67 x 40 mm
<b>Weight (without batteries)</b>	97 g
<b>Classification</b>	Security grade 2/Environmental class II (EN 50131-1)
<b>Environment</b>	Indoor general
<b>Operating temperature range</b>	-10 °C do +40 °C
<b>Average operating humidity</b>	75% RH, without condensation
<b>Certification body</b>	Trezor Test (no. 3025)

**In compliance with**

EN IEC 63000, EN 50130-4, EN 55032, EN IEC 62368-1, ETSI EN 300 220-1, -2, EN 50131-1, EN 50131-5-3, EN 50131-4, EN 50131-6

**Recommended screw**

3 x   $\varnothing$  3,5 x 40 mm (flat head)